


**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>B65D 6/16</b>	<b>A1</b>	(11) International Publication Number: <b>WO 97/39954</b> (43) International Publication Date: 30 October 1997 (30.10.97)
<p>(21) International Application Number: PCT/SE97/00604</p> <p>(22) International Filing Date: 10 April 1997 (10.04.97)</p> <p>(30) Priority Data: 9601513-6      22 April 1996 (22.04.96)      SE</p> <p>(71) Applicant (for all designated States except US): PERSTORP AB [SE/SE]; S-284 80 Perstorp (SE).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): BRAUNER, Manfred [AT/AT]; Spohrstrasse 55, A-1130 Wien (AT).</p> <p>(74) Agent: STENBERG, Yngve; Perstorp AB, S-284 80 Perstorp (SE).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>

(54) Title: COLLAPSIBLE CONTAINER



## (57) Abstract

Collapsible container for transport and storage, comprising a bottom part (2) and side walls (1) movably connected to the bottom part (2) via hinges (3) which are formed by lower hinge-parts (3') and upper hinge-parts (3''). The hinge-parts (3', 3'') are integrated with their respective part (1, 2). Two side walls (1), placed on opposite sides are provided with an inwards angled edge (4') at each of their two ends. The edges (4') connect, when in upright position, with the adjoining side walls (1). The inwards angled edges (4') are provided with a number of coupling devices (5) which are intended to interact with corresponding couplings (6) placed at the ends (4'') of the adjoining side walls (1). The side walls (1) can hereby be locked together in an upright position. At least two opposite side walls (1), preferably all four, are provided with hollow channel-like reinforcing profiles (7) stretching along three sides of each of the side walls (1), wherein one of the sides is always an upper side (8).

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

### C llapsible container

The present invention relates to a collapsible container for transport and storage.

Containers made from different materials such as wood, metal, plastic etc. are frequently used. One problem with such containers are that they often demand the same transport volume when returned to the source as when delivered with goods.

An alternative to the return transport is a so-called one way package which is disposed of after delivery.

Another common way to solve the problem is to provide the package with a so-called nesting function. This means that empty containers are partly placed in one another, by providing the containers with sloping sides.

Yet another way to solve the problem is to dismantle or fold the sides of the container. The mostly known side dismantling is the pallet and pallet collar. An example of commonly used containers with foldable sides is the collapsible pallet container. The sides are here made foldable by attaching their respective lower end to the bottom part via a hinge.

A disadvantage with this type of container is that the load carrying ability is radically impaired when compared to solid, non-collapsible containers. This is mainly due to the fact that the corner parts, on non-collapsible containers taking up around 80% of the weight from above, are parted on collapsible containers. Since these load carrying corners are parted on collapsible containers, this will have to be compensated for by adding reinforcing ribs on the sides. This will, besides added weight, also cause difficulties when cleaning the container due to the number of small pockets that are formed between the ribs.

According to the present invention is it possible to manufacture a collapsible container where the above mentioned disadvantages are avoided. The invention relates to a collapsible container for transport and storage, comprising a bottom part and inwards foldable side walls. The parts are manufactured by injection moulding of a thermoplastic material. The invention is characterised in that the side walls are movably connected to the bottom part by hinges. The hinges are formed by a number of lower hinge-parts which are manufactured in one piece together with the bottom part and a number of upper hinge-parts which are manufactured in one piece together with the foldable side walls. Two side walls, placed on opposite sides, preferably the two long-side walls are provided with an inwards angled edge at each of their two ends. The edges connect with the adjoining side walls, preferably the short-side walls, when in an upright position. The inwards angled edges are provided with a number of coupling devices which are intended to interact with corresponding couplings placed at the ends of the

adjoining side walls so that the side walls can be locked together in an upright position. At least two opposite side walls, suitably the long-side walls, preferably all four side walls, are provided with a hollow channel-like reinforcing profiles which stretches along at least three sides of each of the side walls, wherein one of the sides always is a the upper side. The reinforcing hollow profiles will hereby constitute an effective replacement for the reinforcing rib profiles that normally are used, whereby a lighter and more hygienic design is achieved. The hollow profiles can suitably be achieved by substantially filling the mould with molten thermoplastic material from an injection nozzle. The molten thermoplastic material is then allowed to solidify somewhat on the surface closest to the inner walls of the mould cavity. A pressurised gas is thereafter injected through an intake suitably placed at one end of the profile. The gas is allowed to flow into the still molten plastic in the core of the profile wherein a cavity is formed in the profile. The still molten plastic is hereby ejected from of the mould cavity. A container of this type can suitably be made from a polymer material from the group, polyethylene, polypropylene, polyamide, polystyrene, acryle-butadiene-styrene, poly-alkylene-terephthalate or the like.

Suitably at least two opposite side walls, preferably all four, are provided with handle openings close to their respective upper sides. The handle openings are placed so that the reinforcing profiles form the upper edge of the handle.

The short-side walls are preferably provided with guiding and load-transferring guiding organs which are intended to interact with corresponding receiving means placed on the inside of the two inwards angled edges of the long-side walls. The shearing stress between two adjoining walls will hereby be transferred more effectively so that stress on the coupling means is decreased.

The bottom part is preferably, as seen from above, provided with recessed support profiles along the edges. The support profiles are usually provided with draining holes. The lower surface of said support profiles forms the support surface of the container. The support profiles also limit side-ways shifting when containers are stacked upon one-another. The long-side walls are preferably provided with inwards recessed sections at their lower edges, as seen when in an upright position. The recesses are intended to receive the support profiles when containers are stacked with the side walls in a down-folded position.

The coupling devices are preferably manufactured in one piece together with the short-side walls. The coupling devices preferably include a locking lip placed on the outer end of one side of a rib, which rib on both sides are enclosed by holes. A

spring rib runs from the farther end of one of the holes to the other side of outer side of the rib.

The invention is explained further together with enclosed drawings, all showing the same embodiment of the invention wherein,

-figure 1 shows, in perspective seen from above, a collapsible container with the side walls 1 in an upright position.

-figure 2 shows, in perspective, a part of a hinge between a side wall 1 and a bottom part 2.

-figure 3 shows, in perspective, a part of a long-side wall with receiving means.

-figure 4 shows, in perspective, a part of a short-side wall with guiding means.

-figure 5 shows, in perspective, a part of the bottom part 2 seen from the inside.

Figure 1 shows one embodiment of a collapsible container according to the invention. The collapsible container comprises one bottom part 2 and collapsible side walls 1. The parts 1, 2 are manufactured by injection moulding of a thermoplastic material. The side walls 1 are movably connected to the bottom part 2 via hinges 3. The hinges 3 are formed by a number of lower hinge-parts 3' (figure 2) which are manufactured in one piece together with the bottom part 2, and a number of upper hinge-parts 3'' (figure 2) which are manufactured in one piece together with their respective, foldable side walls 1. Both of the two long-side walls 1', 1'' are provided with an inwards angled edge 4' at each of their two ends. The edges 4' connect with the adjoining short-side walls 1''', 1'''''. The inwards angled edges 4' are provided with a number of coupling devices 5 (figure 4) which are intended to interact with corresponding couplings 6 (figure 3) placed at the ends 4'' of the adjoining short-sides 1''', 1'''''. All four of the side walls 1 are provided with a channel-like, hollow reinforcing profile 7 which runs along the two vertical sides and the upper horizontal side 8 of the side walls 1.

Figure 2 shows in perspective a hinge between a side wall 1 with upper hinge-parts 3'' and a bottom part 2 with lower hinge-parts 3'.

Figure 3 shows in perspective a part of a long-side wall 1', 1'', while figure 4 shows in perspective, a part of a short-side wall 1''', 1'''''. The short-side walls 1''', 1''''' (figure 4) are at both their ends 4'' provided with guiding and load-transferring

means 10" which are intended to interact with corresponding receiving means 10' (figure 3) placed on the inside of the inwards angled edges 4' of the two long-side walls 1', 1". The coupling devices 5, which are manufactured in one piece together with the short-side walls 1'", 1''' include a locking lip 14 placed on the outer end of a first side of a rib 15. The rib is on both sides enclosed by holes 16', 16 ". A spring rib 17 runs from the farther edge of one hole 16" to the second side of the outer end of the rib 15.

Figure 5 shows in perspective a part of a bottom part 2 seen from the inside. The bottom part 2 is along its edges provided with recessed support profiles 11, provided with draining holes 12. The lower surface of the support profiles 11 forms the support surface of the container. The support profiles also limit side-ways shifting when containers are stacked upon one another. The long-side walls 1', 1" (figure 1) are provided with inwards recessed sections 13 at their lower edges, as seen when in an upright position. The recesses 13 are intended to receive the support profiles 11 (figure 5) when containers are stacked upon one another with the side walls 1 in a down-folded position.

The invention is not limited to the embodiment shown, since it can be varied in different ways within the scope of the invention.

**CLAIMS**

1. Collapsible container for transport and storage, comprising a bottom part (2) and inwards foldable side walls (1), which parts (1, 2) are manufactured through injection moulding of a thermoplastic material, **characterised in that** the side walls (1) are movably connected to the bottom part (2) via hinges (3), formed by a number of lower hinge-parts (3') which are manufactured in one piece together with the bottom part (2) and a number of upper hinge-parts (3'') which are manufactured in one piece together with the foldable side walls (1), that two side walls (1), placed on opposite sides, preferably the two long-side walls (1', 1''), are provided with an inwards angled edge (4') at each of their two ends, which edges (4') in an upright position connect with the adjoining side walls (1), preferably the short-side walls (1''', 1'''), that the inwards angled edges (4') are provided with a number of coupling devices (5) which are intended to interact with corresponding couplings (6) placed at the ends (4'') of the adjoining side walls (1) so that the side walls (1) can be locked together in an upright position, and that at least two opposite side walls (1), suitably the long-side walls (1', 1''), preferably all four side walls (1', 1'', 1''', 1''') are provided with a hollow channel-like reinforcing profile (7) which runs along at least three sides of each of the side walls (1), wherein one of the sides is always an upper side (8).
2. Collapsible container according to claim 1 **characterised in that** at least two opposite side walls (1), preferably all four, are provided with handle openings (9) close to the respective upper sides (8) and that handle openings (9) are placed so that the reinforcing profile (7) forms the upper edge of the handle.
3. Collapsible container according to claim 1 or 2 **characterised in that** the short-side walls (1''', 1''') are provided with guiding and load-transferring guiding means (10'') which are intended to interact with corresponding receiving means (10') placed on the inside of the two inwards angled edges (4') of the long-side walls (1', 1'').
4. Collapsible container according to any of the claims 1 - 3 **characterised in that** the bottom part (2) is provided with recessed support profiles (11), as seen from above, along the edges, which support profiles (11) are provided with draining holes (12), that the lower surface of said support profiles (11) forms the support surface of the container and that it limits side-ways shifting when containers are stacked upon one-another.

5. Collapsible container according any of the claims 1 - 4 **characterised in that** the long-side walls (1', 1'') are provided with recessed sections (13) at their lower edges which are intended to receive the support profiles (11) when containers are stacked with the side walls (1) in a down-folded position.
6. Collapsible container according to any of the claims 1 - 5 **characterised in that** the coupling devices (5), which are manufactured in one piece together with the short-side walls (1''', 1'''), include a locking lip (14) placed on the outer end of one side of a rib (15), which rib (15) on both sides are enclosed by holes (16', 16''), and that a spring rib (17) runs from the farther end of one of the holes (16'') to the other side of the outer side of the rib (15).



1/3




Fig. 2

2/3




Fig. 3




Fig. 4





Fig. 5



## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/SE 97/00604

## A. CLASSIFICATION OF SUBJECT MATTER

IPC6: B65D 6/16  
According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0067323 A2 (FRIEDRICH, UWE W), 22 December 1982 (22.12.82), figures 1-3, abstract --	1-6
X	US 4917255 A (FOY ET AL), 17 April 1990 (17.04.90), figures 1-14, abstract --	1,3
A	EP 0091718 A1 (CURVER B.V.), 19 October 1983 (19.10.83), figures 1-3, abstract -- -----	1-6

☐ Further documents are listed in the continuation of Box C. ☒ See patent family annex.

- \* Special categories of cited documents:
- "A" document defining the general state of the art which is not considered to be of particular relevance
- "B" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

23 July 1997

Date of mailing of the international search report

01-08-1997

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Helena Akerlund  
Telephone No. +46 8 782 25 00

# INTERNATIONAL SEARCH REPORT

Information on patent family members

01/07/97

International application No.

PCT/SE 97/00604

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
EP	0067323	A2	22/12/82	DE 8117370 U	24/12/81
				DE 8119990 U	24/12/81
US	4917255	A	17/04/90	CA 2007900 A,C	24/08/90
				EP 0385914 A,B	05/09/90
				SE 0385914 T3	
				FI 95017 B	31/08/95
				JP 2242741 A	27/09/90
				JP 6033086 B	02/05/94
				NO 173694 C	19/01/94
				PL 163723 B	29/04/94
EP	0091718	A1	19/10/83	DE 8310454 U	22/09/83
				NL 8201534 A	01/11/83